



















WBCA Product Number	Description	WBCA Product Number	Description	WBCA Product Number	Description
 <b>WBCA ROOF HATCH</b>	<b>Roof Hatch.</b> 14 gauge galvanized steel, durable re-coatable gray primer finish, highly visible safety caution striping, heavy duty lock and handle, weather-resistant gasketing. <b>Available in many sizes</b>	 <b>TYPE J &amp; JD</b>	<b>Floor Hatch.</b> Single or double leaf covers are constructed of 1/4" diamond pattern plate and reinforced for a 300 lb/ft2(1464 kg/m2) liveload. Features reinforced composite spring tubes, heavy forged brass hinges, and zinc plated/chromate sealed hardware. By Bilco.	 <b>WBCA SAFETY GRAB</b>	<b>WBCA Safety Grab:</b> 3/4" heavy gauge steel that attaches to the roof hatch or added and improved safety whether entering or leaving the roof. Overall height 17", horizontal width 10" to corner, Textured for increased grip.
 <b>TYPE S &amp; E</b>	<b>Roof Hatch.</b> The easy one-hand operation to the fully open or closed position provides the user the security of having one hand firmly on the ladder at all times. Available in galvanized steel, aluminum, or stainless steel construction. By Bilco.	 <b>TYPE T &amp; TD</b>	<b>Floor Hatch.</b> Aluminum non-drainage door accepts carpet and composition flooring material 1/8" or 3/16" in thickness. Single or double leaf doors are virtually hidden in interior applications. By Bilco.	 <b>WBCA SAFETY POST</b>	Provide easier, safer ladder access through roof hatches, floor, vault, and sidewalk doors, and manholes. Telescoping post permanently mounts to the top two rungs of any fixed ladder providing a positive hand-hold enabling the user to enter or exit an opening in an upright and balanced position.
 <b>TYPE DSH</b>	<b>Automatic Fire Vent.</b> DSH series fire vents are available in a number of standard UL-listed and FM-approved sizes. Features include fully insulated covers and galvanized steel or aluminum construction. By Bilco.	 <b>TYPE TER &amp; TRD</b>	<b>Floor Hatch.</b> Aluminum non-drainage door accepts architectural flooring material. Similar to Type T in function, these single and double leaf doors are designed with a pan cover to accept a variety of flooring materials up to 1" in thickness. By Bilco.	 <b>BILCO LADDERUP</b>	The Bilco LadderUP is furnished completely assembled, ready to mount on rear of ladder with clamp brackets on climbing side
 <b>TYPE SV</b>	<b>Fire Vent.</b> For applications requiring smaller vents, single leaf models are available in galvanized steel or aluminum construction and can be provided with polycarbonate domes for added daylight. By Bilco.	 <b>TYPE Q</b>	<b>Floor Hatch.</b> Steel non-drainage single leaf covers are constructed of 1/4" diamond pattern plate and reinforced for a 150 lb/ft2 (732 kg/m2) live load. Features zinc plated and chromate sealed hardware, concealed hinges, and the T-CAM® lifting system for ease of operation. By Bilco.	 <b>CLASSIC SERIES</b>	<b>Residential Basement Door.</b> Heavy-duty steel construction, Flow-coated, baked-on factory prime finish, Corrosion-resistant zinc-plated, chromate-sealed hardware, Torsion Cam Lift system provides easy, one-hand operation, Slide bolt locking mechanism.
 <b>TYPE FR &amp; FRLC</b>	<b>Fire Rated Floor Hatch.</b> Maintains the fire rating of a 2-hour floor/ceiling assembly where access is required between building floors. Includes an optional UL Listed automatic closing system, intumescent fire resistant coating. By Bilco	 <b>TYPE K &amp; KG</b>	<b>Floor Hatch.</b> Aluminum non-drainage door single or double leaf covers, constructed of 1/4" diamond pattern plate, reinforced for a 150 lb/ft2(732 kg/m2) live load. Features zinc plated, chromate sealed hardware, concealed hinges, and T-CAM® lifting system. By Bilco.	 <b>ULTRA SERIES</b>	<b>Residential Basement Door.</b> The beauty of a wooden door, without the work. Made from high-density polyethylene and engineered to exacting specifications, the Ultra Series door provides safe and code-compliant basement access, weather-tight performance and easy operation . By Bilco
 <b>WBCA OK500/501</b>	<b>Aluminum Fixed Access Ladder</b> Sleek design eliminates bulky springs for easier access of large objects. Comparable clearance to traditional 25" wide models. By O'Keefe.	 <b>WBCA RAILING</b>	<b>WBCA GUARD RAILING SYSTEM:</b> Finish Galvanized (hot dipped). Chain system 3/16" proof coil ASTM specification, zinc plated with quick link and "S" hookSelf closing gate (optional to chain) Manufacturer's standard spring or gravity operated.		
 <b>DISAPPEARING ATTIC</b>	Disappearing Attic or Roof Access Ladder. By <b>Precision Ladders, LLC</b>				

