

The Williams Brothers Corporation of America (the "Seller") provides the following warranty of its goods: All goods sold hereunder are warranted to be free from defects in material and workmanship for a period of one (1) year. The purchaser agrees that he will inspect the goods upon delivery. Every claim for defective material or workmanship or negligence or from any other cause shall be deemed waived by the purchaser unless made to the Seller in writing within ninety (90) days of the date of shipment from purchaser to purchasers' customer provided that all such claims for goods restocked for resale must be submitted in writing to the Seller within one (1) year from receipt by purchaser of the goods to which such claims relate. Defective goods for which a valid claim has been made shall be returned to the Seller and defective goods so returned will be replaced or repaired without

charge, but the Seller shall not be liable for any other loss, damage or expense, **INCLUDING BUT NOT LIMITED TO CONSEQUENTIAL DAMAGES**, directly or indirectly arising from the condition or use of the goods or from any other cause, the exclusive remedy against the Seller being to require the replacement or repair of defective goods. **THIS WARRANTY IS THE SOLE AND EXCLUSIVE WARRANTY PROVIDED TO THE PURCHASER. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION OF THE FACE HEREOF. THE SELLER HEREBY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS AND IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

## Temperature Rise

Over the past several years I have had the opportunity of being involved with the application of both insulated and non-insulated fire-rated steel access doors. I find it alarming that local and national code officials, architects, builders and dealers are confused over the proper use of insulated and non-insulated fire-rated steel access doors.

It is important to note that steel access doors come in three varieties of fire rating and fire-stopping capabilities:

**UNARMED** —Used when fire integrity between areas of a building is not a design criterion.

**FIRE-RESISTANT** — Doors in this classification are neither tested nor labeled by a third party. However, the construction inherent in the design is similar to fire-rated doors.

**FIRE RATED** — These doors are specified for use in wall openings when the passage of fire must be retarded. They are made using either Underwriters Laboratory (UL) or Warnock Hersey approved plans and materials. They carry a third party label showing the fire rating as follows:

**Class A** — Openings in fire walls and in walls that divided a single building into fire areas.

**Class B** — (1-hour and 1 1/2-hour ratings) Openings in enclosures of vertical communications through building and in 2-hour rated partitions providing horizontal fire separations.

**Class C, D, E** — Less critical fire rating applications.

