



Project: Date: Contractor: Architect Quantity:_ App Initials:

1330 Progress Drive • Front Royal, VA 22630 • Phone: 1-800-255-5515 • WWW.Wbdoors.com



The watertight (floodtight/gastight) angle frame floor access door is designed for interior and exterior applications where water and gas-tightness are required.

Cover: 1/4" diamond plate reinforced for 1560 PSF live loads (capable of holding up to 25 ft head of water)

Frame: Angle type with strap anchors

Hardware: All 316 SS nuts, bolts and washers

Security: SS flood tight cam locks

Finish: Aluminum cover and frame have mill finish which is protected during shipping and installation by an attached adhesive-backed vinyl material. All parts of the frame in contact with concrete have a coating of bituminous paint

Hold-Open Device: 316 SS Hold-open arm with secondary

latch mechanism

Lift Handle: Flush and floodtight lift handle

Installation: Installation shall be in accordance with the

manufacturer's instructions

OPTIONS (at addition cost)

☐ Steel

■ Stainless Steel

■ Double door

Special sizes available upon request

	Model No.	Size (inches) W x L	Ship Wt. Lbs.
	W-APS 8100	24 x 24	65
	W-APS 8100	24 x 30	80
	W-APS 8100	24 x 36	90
	W-APS 8100	30 x 30	90
	W-APS 8100	30 x 36	105
	W-APS 8100	30 x 48	130
	W-APS 8100	36 x 36	120
	W-APS 8100	36 x 48	145
	W-APS 8100	42 x 42	135
	W-APS 8100	48 x 48	160

Double door available upon request. Steel available upon request. Call for submittal sheet.





STRAP ANCHORS