


SUBMITTAL SHEET



FRONT ELEVATION

**Paddle latch
w/2 keys**

SECTION DETAIL


SECTION DETAIL

Fire-rated access door for ceiling installation for 3 hr max size 24 x 36.

This fire-rated door can be used wherever it is necessary to provide service access to shafts and any other location which must have a fire rating. Approved ceiling use.

UL Listed "B" label for 1-1/2 hours (vertical).
Warnock-Hersey listed for 3 hours (horizontal).

NOTE: For fire-rated ceiling access doors, on size 16" x 16" and larger, extra spring supplied with door must be attached from back of door pan to framing or floor above. In horizontal (ceiling) applications door has self-assisted closing.



**** Hot Smoke Seal™** fire tested: Listed to meet the requirements of standards UL10B, UL10C, UBC 7-2, Part 1 and BS476: 1987 for application to fire rated door assemblies. Tested for smoke controlled assemblies: Listed to meet the requirements of standards UL1784, NFPA 105, UBC 7-2, Part 2, and BS476:Part 31, Section 31.1:1983.

It also is a chemically inert, highly stable, expandable graphite strip, tested and proven in positive pressure conditions to withstand both hot smoke and hot gasses, resulting in the longer integrity of a door assembly. More economical to use than specially modified doors in "tested assembly only" classifications. Chemically inert, and therefore will not degrade from carbon dioxide and ozone like the many intumescent being offered by other manufacturers.

Hot Smoke Seal™ is not affected by moisture and will not break down like fiber or cellulose based products and does not require periodic after market field inspections.

Insulation: is a rigid mineral wool (stone wool) insulation board for high temperature industrial applications subject to light mechanical loads.] - 2" thickness.

SPECIFICATIONS:

Door: 14 ga. steel, drywall bead

Trim: 16 ga. steel, 1" wide perforated flange of 24 ga. galvanized material for mounting purposes, 2 1/2" deep

Finish: Primed white baked enamel, paintable surface

Latch: Spring loaded sliding bolt type, paddle latch. 2 keys per door keyed alike

Hinge: Fully concealed, pivot rod type hinge. Allows opening to 140°

Insulation: 2" thick mineral wool in between two pieces of steel

Ceiling Installation: Largest size acceptable is up to and including 24" x 36"

OPTIONS [at additional cost]

Finishes:

- ☐ Stainless Steel Type 304 No. 4 Satin Finish Brushed
- ☐ Stainless Steel Type 316 No. 4 Satin Finish Brushed

Options: [additional cost]

- ☐ Mortise lock and locks by others
- ☐ Hot Smoke Seal* gasket all 4 sides
- ☐ Special sizes available
- ☐

✓	Model No.	Door Size W x H	Wall Opening	Paddle Latch	Ship Wt. Lbs.
	FR DW 820	8 x 8	8 1/4 x 8 1/4	1	8
	FR DW 820	10 x 10	10 1/4 x 10 1/4	1	10
	FR DW 820	12 x 12	12 1/4 x 12 1/4	1	12
	FR DW 820	12 x 18	12 1/4 x 18 1/4	1	15
	FR DW 820	12 x 24	12 1/4 x 24 1/4	1	19
	FR DW 820	14 x 14	14 1/4 x 14 1/4	1	14
	FR DW 820	16 x 16	16 1/4 x 16 1/4	1	17
	FR DW 820	18 x 18	18 1/4 x 18 1/4	1	21
	FR DW 820	18 x 24	18 1/4 x 24 1/4	1	26
	FR DW 820	20 x 30	20 1/4 x 30 1/4	1	24
	FR DW 820	22 x 22	22 1/4 x 22 1/4	1	28
	FR DW 820	22 x 24	22 1/4 x 24 1/4	1	29
	FR DW 820	22 x 30	22 1/4 x 30 1/4	2	39
	FR DW 820	22 x 36	22 1/4 x 36 1/4	2	47
	FR DW 820	24 x 24	24 1/4 x 24 1/4	1	32
	FR DW 820	24 x 30	24 1/4 x 30 1/4	2	43
	FR DW 820	24 x 36	24 1/4 x 36 1/4	2	48
	FR DW 820	24 x 48	24 1/4 x 48 1/4	2	62
	FR DW 820	30 x 30	30 1/4 x 30 1/4	2	48
	FR DW 820	32 x 32	30 1/4 x 32 1/4	2	55
	FR DW 820	36 x 36	36 1/4 x 36 1/4	2	58
	FR DW 820	36 x 48	36 1/4 x 48 1/4	2	62
	FR DW 820	48 x 48	48 1/4 x 48 1/4	2	68

*** Wall installation only**

RELATED PRODUCTS

**WB FR 800 Series
Standard Fire-
Rated**



WBdoors.com

BuyOnline
WBCA 2023



The World's Largest Access Door Store.™

Project: _____ Date: _____
Contractor: _____ Architect: _____
Sizes: _____ Quantity: _____ App Initials: _____

1330 Progress Drive • Front Royal, VA 22630 • Phone: 1-800-255-5515 • www.wbdoors.com