


SUBMITTAL SHEET

WALLS & CEILINGS

FRONT ELEVATION

SECTION DETAIL



WELDED, CORROSION RESISTANT ALUMINUM FRAME Supplied with 5/8" drywall, precision installed in door 0.06" GAP BETWEEN FRAME AND DOOR 0.06" GAP BETWEEN FRAME AND DOOR

SPECIFICATIONS:

Door & Frame: Lightweight Welded Aluminum Removable Door: Fully Detachable Hatch/Door Finish: Recessed 5/8" or 1/2" for Tile Latches: Heavy Duty Concealed Touch Latches Hinges: Concealed Hinge with fully removable door


Standard Features:

- · Easy assembly
- · Solid aluminium frame
- Flush installation in walls

OPTIONS (AT ADDITIONAL COST)

☐ WB Key Cylinder Locks - keyed alike 2 keys per door





•	Model No.	Door Size	Cut Opening	Ship Wt. Lbs.
	DWAL 414	8 x 8	8 3/8 x 8 3/8	5
	DWAL 414	10 x 10	10 3/8 x 10 3/8	7
	DWAL 414	12 x 12	12 3/8 x 12 3/8	8
	DWAL 414	14 x 14	14 3/8 x 14 3/8	13
	DWAL 414	16 x 16	16 3/8 x 16 3/8	15
	DWAL 414	18 x 18	18 3/8 x 18 3/8	17
	DWAL 414	20 x 20	20 3/8 x 20 3/8	20
	DWAL 414	24 x 24	24 3/8 x 24 3/8	24
	DWAL 414	24 x 36	24 3/8 x 36 3/8	35

Custom sizes available upon request. Sizes larger than 40x40 are Double Door. 1.03" **OPEN PIN HINGE** REMOVABLE DOOR 1.58" 5/8 1.26" CONCEALED TOUCH LATCH (2 PER DOOR, CLOSER TOGETHER ON SMALLER DOORS)

Project:		Date:
Contractor:	_Architect:	
Sizes:	Quantity:	App Initials:

1330 Progress Drive • Front Royal, VA 22630 • Phone: 1-800-255-5515 • WWW.Whdoors.com



WB DW 400 Series for Drywall





